

Upgrades



NEMA 4 Protection Upgrade

DS500

ABS and acrylic shrouds over vent ports, cable ports and fan/filter inlet to protect against heavy airborne particulate or water falling from the top or sprayed down sides (such as in wash down environments for food processing).

Heavy airborne particulate like wood shavings, cotton fibers, paper dust, etc. easily clogs your filter, limiting filtration and circulation. Shrouds require the air to be pulled in from the bottom to prolong filter life and effectiveness.



Security Upgrade

Add three locking doors, unbreakable polycarbonate window and security hardware (where applicable) to your enclosure. Ideal for customers with high traffic production areas, storing blank checks, sensitive documentation or tools.

DS650 1 door enclosures

DS650C 2 door enclosures

DS650CRK 3 door enclosures

DS650CRK 3+ door enclosures



Enclosure Cooling Upgrade

A 6,000 BTU AC w/ Internal Thermostat Control keep computers operational in temperatures up to 150F.

Tested by customers in metal industries, foundries and Warehouses w/o air conditioning.

The AC occupies included base cabinet (no additional storage). Removable drip pan. Extremely high humidity environments may occasionally require drainage hose.

DS985 6000 BTU A/C w/ Base

DS705 Extra Fan

Upgrades



Enclosure Heating Upgrade

DS1500

Internal, Thermostat Controlled Enclosure Heater keeps your equipment at operational temperatures in the coldest of environments.

200 Watt Industrial coated bulb heater

DS675 Internal Power Receptacle



Power Upgrade

Manage power distribution and cabling inside enclosure.

Front Mounted, illuminated power switch pre-wired to internal 2320 joule, 7 outlet Belkin surge protector with 8 ft industrial power cord.

DS675 Internal Power Receptacle

DS695 Surge Protector

DS690 675 + External Power Switch



Monitor Upgrade

Increase enclosure size to accommodate 19" monitor. This will increase the enclosures width by 2" and height by 2".

DS1019 19"

DS1021 21"

Upgrades



Touch Screen Upgrade

DS875

To modify a standard enclosure to accommodate a Touch Screen Monitor, the acrylic window is removed to give access to the touch screen and the monitor is restrained against a 1.5" closed-cell foam gasket to seal the enclosure.

Please be sure to complete our measuring guide.



F/C Digital Temperature Display

DS475

Large digital display to monitor the enclosure's internal temperature.

Features user specified high temp / low temp alarms.
Requires one AAA battery